

Blendungsbewertung nach UGR

ρ Decke		70	70	50	50	30	70	70	50	50	30
ρ Wände		50	30	50	30	30	50	30	50	30	30
ρ Boden		20	20	20	20	20	20	20	20	20	20
Raumgröße X Y		Blickrichtung quer zur Lampenachse					Blickrichtung längs zur Lampenachse				
2H	2H	16.7	18.1	17.0	18.3	18.5	16.8	18.1	17.1	18.3	18.6
	3H	18.3	19.5	18.6	19.8	20.0	18.4	19.6	18.7	19.8	20.1
	4H	18.9	20.1	19.3	20.3	20.6	19.0	20.2	19.4	20.4	20.7
	6H	19.4	20.4	19.7	20.7	21.0	19.5	20.6	19.9	20.9	21.2
	8H	19.5	20.5	19.9	20.8	21.2	19.6	20.7	20.0	21.0	21.3
	12H	19.6	20.6	20.0	20.9	21.2	19.7	20.7	20.1	21.0	21.4
4H	2H	17.4	18.6	17.8	18.8	19.1	17.5	18.6	17.8	18.9	19.2
	3H	19.2	20.1	19.5	20.5	20.8	19.2	20.2	19.6	20.5	20.9
	4H	19.9	20.8	20.3	21.1	21.5	20.0	20.9	20.4	21.2	21.6
	6H	20.5	21.2	20.9	21.6	22.0	20.6	21.4	21.0	21.7	22.1
	8H	20.7	21.4	21.1	21.8	22.2	20.8	21.5	21.3	21.9	22.3
	12H	20.8	21.5	21.3	21.9	22.3	21.0	21.6	21.4	22.0	22.4
8H	4H	20.2	20.9	20.7	21.3	21.7	20.3	21.0	20.7	21.4	21.8
	6H	20.9	21.5	21.4	21.9	22.4	21.0	21.6	21.5	22.1	22.5
	8H	21.2	21.7	21.7	22.2	22.7	21.3	21.8	21.8	22.3	22.8
	12H	21.4	21.9	21.9	22.3	22.8	21.5	22.0	22.0	22.4	22.9
12H	4H	20.3	20.9	20.7	21.3	21.7	20.3	21.0	20.8	21.4	21.8
	6H	21.0	21.5	21.5	22.0	22.4	21.1	21.6	21.6	22.1	22.5
	8H	21.3	21.8	21.8	22.2	22.7	21.4	21.9	21.9	22.3	22.8

Variation der Beobachterposition für Leuchtenabstände S

S = 1.0H	+0.1 / -0.1	+0.1 / -0.1
S = 1.5H	+0.2 / -0.3	+0.2 / -0.3
S = 2.0H	+0.4 / -0.6	+0.4 / -0.6
Standardtabelle	BK06	BK06
Korrektursummand	4.1	4.2

Korrigierte Blendindizes bezogen auf 3431lm Gesamtlichtstrom